

# ALKYD UNDERCOAT

Product Data Sheet (Revised 11/11/21)

## PRODUCT CATEGORY

Interior Alkyd Enamel Undercoat

## PRODUCT CODE

1-35-0677

## DESCRIPTION

Alkyd flat, off-white coat

## RECOMMENDED USE

New or previously painted interior wood, plaster, and drywall of both residential and commercial buildings.

## FEATURES AND BENEFITS

- Good sealing
- Good coverage.
- Ease sanding

## PACKAGING

3.78 can and 1.0 L Can

## PRODUCT DATA

**Resin Types:** Alkyd

**Volume Solid:** 45%  $\pm 2\%$

**Weight Solid:** 68%  $\pm 2\%$

**VOC:** <450 g/L

**Density:** 1.37 kg/L



## PRACTICAL COVERAGE

10-12 m<sup>2</sup> /liter/coat for dry film thickness at ~1.5 mils.

Actual coverage may vary depending on the type, age and texture of the substrate and application method.

## DRY TIME AT 25 °C

- To touch: 4-6 hours
- To recoat: 24 hours
- Low temperature, poor ventilation will increase these times.

## GENERAL SURFACE PREPARATION

Surface must be dry and clean. Remove all dust, mildew, oil, loose wood fibers and other contaminants. Remove loose, peeling stain by sanding, scraping or wire brushing. Remove grade stamps or pencil mark by sanding.

## LIMITATIONS OF USE

This product is not recommended for exterior use. Do not use directly on masonry surfaces such as bricks, blocks, concrete.

## CLEAN-UP SOLVENT

Mineral Spirits

## SHELF LIFE

2 years maximum-unopened

## DISPOSAL

Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

## DISCLAIMER

The technical data furnished above by the Consolidated Coatings Company is provided for information purposes only and is, to the best of our knowledge. Since application methods and conditions are beyond our control, we cannot offer a guarantee or warranty, representation, or condition, express or implied, whether arising by statute, by operation of law, or otherwise, (including merchantability or fitness for a particular purpose) with respect to this product and we assume no responsibility or liability of any kind for coverage, performance or damage (whether arising from negligence of the vendor or otherwise) resulting from the installation, operation, use or performance of this product.

