

# ANTI-CORROSIVE PRIMER

Product Data Sheet (Revised 24/11/21)

**PRODUCT CATEGORY**

Industrial Maintenance

**PRODUCT CODE**

50-2050

**DESCRIPTION**

Recommended for exterior and interior ferrous metal surfaces. This is an alkyd primer with corrosion resistant properties. Use on machinery, piping, heavy equipment and industrial metal.

**RECOMMENDED USE**

Ferrous Metal Surfaces, Aluminum Metal Surfaces.

**FEATURES AND BENEFITS**

Quick Dry time, fast recoat.

**PACKAGING**

3.7 L Can, 18.9 L Pail

**TINT AND BASE INFORMATION**

Not Tinted, Grey

**PRODUCT DATA**

**Gloss:** Flat

**VOC:** 669 g/l

**Coverage:** Approx. 530 sq ft / gal at 1 mil DFT

**DFT:** 1 mil to 2 mil recommended

**Weight-Volume:** Approximately 1.3 kg/ litre

**Volume-Solids:** Approximately 35% solids by volume

**Weight-Solids:** Approximately 57% solids by weight

**Drying Time:** Dust free: 15 minutes

(@ 25°C) To Touch: 2 hours Recoat: 2 hours

**Clean up:** Clean with thinners

**MIXING & APPLICATION INFORMATION**

Mix thoroughly before and during use. Air or airless spray application is recommended. (Airless: 1500 psi with 0.01"-0.013" tip) (Brush: Natural Bristle Brush) (Roller: 9-10mm nap, solvent resistant core) Thinning can be used, up to 10% solvent 85-0311 can be used as a reducer for spray application. If desired, up to 10% of 85-0303 solvent can be used in a dip application, if desired, and permitted by local VOC regulations.

**SAFETY**

Proper safety procedures should be followed at all times while handling this product. In confined areas, personal protection equipment and explosion proof application equipment should be used. Keep containers away from heat, flame or sparks when not in use. Use with adequate ventilation. Keep from the reach of children. Read all label directions and Safety Data Sheet for health and safety information prior to use.

**GENERAL SURFACE PREPARATION**

The surface to be coated must be dry, clean and free of oil, grease, release agents and foreign material. SSPC 2 hand cleaning or better is required. For use on metal surfaces.

**LIMITATIONS OF USE**

Apply only when ambient and surface temperatures are above 5 degrees Celsius. For professional use only. Immediately after use place rags, steel wool and waste.

**DISPOSAL**

Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

**DISCLAIMER**

The technical data furnished above by the Consolidated Coatings Company is provided for information purposes only and is, to the best of our knowledge. Since application methods and conditions are beyond our control, we cannot offer a guarantee or warranty, representation, or condition, express or implied, whether arising by statute, by operation of law, or otherwise, (including merchantability or fitness for a particular purpose) with respect to this product and we assume no responsibility or liability of any kind for coverage, performance or damage (whether arising from negligence of the vendor or otherwise) resulting from the installation, operation, use or performance of this product.



7651 Vantage Way, Delta, BC, Canada, V4G 1A6

T: 604-946-7626 | F: 604-946-9609 | TF: 1-800-663-5690