

FAST DRY GREY PRIMER

Product Data Sheet (Revised 24/11/21)

PRODUCT CATEGORY

Industrial Maintenance

PRODUCT CODE

50-6050

DESCRIPTION

A fast dry economical primer for shorter term protection. Use on machinery, piping, heavy equipment and industrial metal.

RECOMMENDED USE

Use for short term protection on fabricated metal and shop work that needs protection in the outdoors.

FEATURES AND BENEFITS

Quick Dry time, fast recoat.

PACKAGING

18.9 L Pail

TINT AND BASE INFORMATION

Not Tinted, Grey

PRODUCT DATA

Gloss: Flat

VOC: 669 g/l

Coverage: Approx. 530 sqft / gal at 1 mil DFT

DFT: 1 mil to 2 mil recommended

Weight-Volume: Approximately 1.3 kg/ litre

Volume-Solids: Approximately 35% solids by volume

Weight-Solids: Approximately 57% solids by weight

Drying Time: Dust free: 15 minutes

(@ 25°C) To Touch: 2 hours, Recoat: 2 hours

Clean up: Clean with thinners

MIXING & APPLICATION INFORMATION

Mix thoroughly before and during use. Air or airless spray application is recommended. (Airless: 1500 psi with 0.01"-0.013" tip) (Brush: Natural Bristle Brush) (Roller: 9-10mm nap, solvent resistant core) Thinning is not required for most applications. If desired, a small amount of 85-0303 solvent can be used if desired and permitted by local VOC regulations.

SAFETY

Proper safety procedures should be followed at all times while handling this product. In confined areas, personal protection equipment and explosion proof application equipment should be used. Keep containers away from heat, flame or sparks when not in use. Use with adequate ventilation. Keep from the reach of children. Read all label directions and Safety Data Sheet for health and safety information prior to use.

GENERAL SURFACE PREPARATION

The surface to be coated must be dry, clean and free of oil, grease, release agents and foreign material. SSPC 2 hand cleaning or better is required. For use on metal surfaces.

LIMITATIONS OF USE

Apply only when ambient and surface temperatures are above 5 degrees Celsius. For professional use only. Immediately after use, place rags, steel wool and waste soaked with the product in a water filled metal container.

DISPOSAL

Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

DISCLAIMER

The technical data furnished above by the Consolidated Coatings Company is provided for information purposes only and is, to the best of our knowledge. Since application methods and conditions are beyond our control, we cannot offer a guarantee or warranty, representation, or condition, express or implied, whether arising by statute, by operation of law, or otherwise, (including merchantability or fitness for a particular purpose) with respect to this product and we assume no responsibility or liability of any kind for coverage, performance or damage (whether arising from negligence of the vendor or otherwise) resulting from the installation, operation, use or performance of this product.



7651 Vantage Way, Delta, BC, Canada, V4G 1A6

T: 604-946-7626 | F: 604-946-9609 | TF: 1-800-663-5690