

FAST DRY PRIMER

Product Data Sheet (Revised 24/11/21)

PRODUCT CATEGORY

Industrial - Coatings

PRODUCT CODE

50-6052

DESCRIPTION

A fast dry alkyd grey primer for interior or exterior steel surfaces.

RECOMMENDED USE

For shop application on interior and exterior structural steel, beams and posts.

FEATURES AND BENEFITS

Low VOC, easy application and clean-up, low odor, greater worker safety to traditional solvent based systems.

PACKAGING

18.9 L Pail, 205 L Drums, 1000 L Totes

TINT AND BASE INFORMATION

Clear and custom colors

PRODUCT DATA

Gloss: Flat – Low Gloss

VOC: 340 g/l

Coverage: Approx. 560 sq.ft. / US gal. 11.25 q. M.L.

DFT: 2 mil or greater recommended

Weight-Volume: Approximately 1.30 kg/ litre

Volume-Solids: Approximately 36% solids by volume

Weight-Solids: Approximately 57% solids by weight

Drying Time: (@ 25°C) Tack Free Dry: 45min., Hard Dry: 3 hours

Clean up: Clean up with 85-0311 (Xylene).

MIXING & APPLICATION INFORMATION

Thinners required: 85-0303 (Mineral Spirits). Not usually required.

This product is mainly applied by spraying. Film Thickness: 1.5 to 2.0 mils dry per coat.

SAFETY

Proper safety procedures should be followed at all times while handling this product. In confined areas, personal protection equipment should be used.

GENERAL SURFACE PREPARATION

The surface should be above 7° C and free of dirt, oil or grease.

LIMITATIONS OF USE

Apply only when ambient and surface temperatures are above 10 degrees Celsius.

CLEAN UP

Clean up with C.C.C 85-0311 (Xylene).

DISPOSAL

Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

DISCLAIMER

The technical data furnished above by the Consolidated Coatings Company is provided for information purposes only and is, to the best of our knowledge. Since application methods and conditions are beyond our control, we cannot offer a guarantee or warranty, representation, or condition, express or implied, whether arising by statute, by operation of law, or otherwise, (including merchantability or fitness for a particular purpose) with respect to this product and we assume no responsibility or liability of any kind for coverage, performance or damage (whether arising from negligence of the vendor or otherwise) resulting from the installation, operation, use or performance of this product.



7651 Vantage Way, Delta, BC, Canada, V4G 1A6

T: 604-946-7626 | F: 604-946-9609 | TF: 1-800-663-5690