

## ACRYLIC URETHANE SAFETY YELLOW BASE

Product Data Sheet (Revised 11/11/21)

### PRODUCT CATEGORY

Acrylic Urethane

### PRODUCT CODE

1-52-2032

### DESCRIPTION

Acrylic Urethane Safety Yellow Base

### RECOMMENDED USE

This acrylic urethane may be used for exterior or interior industrial maintenance, transportation, marine and product finishing applications where corrosion resistance and long-term protection are important. May be used on various metal substrates, wood, plastics, and concrete.

### FEATURES AND BENEFITS

- Excellent resistance to corrosion, abrasion, chemicals, and impact.
- Outstanding gloss and color retention.
- Ease to apply

### PACKAGING

3.78 can and 18.9 L Pail

### PRODUCT DATA

**Resin Types:** Acrylic urethane

**Mixing:** Part A: Part B = 4:1 by volume

**Pot life:** 4 hours

**Gloss:** 85+ at 60 deg.

**Volume Solid:** 60%  $\pm$ 2% on mixed basis

**VOC:** <350 g/L on mixed basis

### DISCLAIMER

The technical data furnished above by the Consolidated Coatings Company is provided for information purposes only and is, to the best of our knowledge. Since application methods and conditions are beyond our control, we cannot offer a guarantee or warranty, representation, or condition, express or implied, whether arising by statute, by operation of law, or otherwise, (including merchantability or fitness for a particular purpose) with respect to this product and we assume no responsibility or liability of any kind for coverage, performance or damage (whether arising from negligence of the vendor or otherwise) resulting from the installation, operation, use or performance of this product.

### PRACTICAL COVERAGE

10-12 m<sup>2</sup> /liter/coat for dry film thickness at 2-3 mils. Actual coverage may vary depending on the type, age and texture of the substrate and application method.

### DRY TIME AT 25 °C

- To touch: 1.5 hours
- To recoat: 3-4 hours
- Low temperature, poor ventilation will increase these times.

### GENERAL SURFACE PREPARATION

Surface to be painted must be clean, dry, and free of oil, grease, and other contamination.

### CLEAN-UP SOLVENT

85-0337 Reducer

### SHELF LIFE

2 years maximum-unopened

### DISPOSAL

Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.



