

## LOW VOC SPEED ENAMEL CLEAR SEMI-GLOSS

Product Data Sheet (Revised 11/11/21)

### **PRODUCT CATEGORY**

Low VOC Alkyd Speed Enamel

### **PRODUCT CODE**

1-55-0070

### **DESCRIPTION**

Alkyd Speed Enamel Clear Semi-gloss

### **RECOMMENDED USE**

For industrial use on all surfaces where a durable, decorative finish is necessary and speed of dry is essential. May apply on machinery, implements, hand tools, racking, shelving and many other uses.

### **FEATURES AND BENEFITS**

- Clear coat, semi-gloss
- Fast drying
- Durable, flexible
- Good gloss and color retention

### **PACKAGING**

3.78 can and 18.9 L Pail

### **PRODUCT DATA**

**Resin Types:** Modified alkyd

**Gloss:** 50-60 at 60 deg.

**Volume Solid:** 27%  $\pm 2\%$

**Weight solid:** 38%  $\pm 2\%$

**VOC:** 356 g/L

### **PRACTICAL COVERAGE**

9-11m<sup>2</sup> /liter/coat for dry film thickness at 1 mil. Actual coverage may vary depending on the type, age and texture of the substrate and application method.

### **DRY TIME AT 25 °C**

- To touch: 30 min
- To recoat: 2 hours
- Low temperature, poor ventilation will increase these times.

### **GENERAL SURFACE PREPARATION**

Surface to be painted must be clean, dry, and free of oil, grease, and other contamination.

### **CLEAN-UP SOLVENT**

85-0311 Reducer

### **SHELF LIFE**

2 years maximum-unopened

### **DISPOSAL**

Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

#### **DISCLAIMER**

The technical data furnished above by the Consolidated Coatings Company is provided for information purposes only and is, to the best of our knowledge. Since application methods and conditions are beyond our control, we cannot offer a guarantee or warranty, representation, or condition, express or implied, whether arising by statute, by operation of law, or otherwise, (including merchantability or fitness for a particular purpose) with respect to this product and we assume no responsibility or liability of any kind for coverage, performance or damage (whether arising from negligence of the vendor or otherwise) resulting from the installation, operation, use or performance of this product.



7651 Vantage Way, Delta, BC, Canada, V4G 1A6

T: 604-946-7626 | F: 604-946-9609 | TF: 1-800-663-5690