

WATER-BASED ALKYD LUMBER END SEAL-CLEAR

Product Data Sheet (Revised 24/11/21)

PRODUCT CATEGORY

Industrial - Wood

PRODUCT CODE

68-9047

DESCRIPTION

A water-based alkyd coating specifically designed for rough or dimensional cut lumber.

RECOMMENDED USE

A water-based coating for use on the ends or surface of dimensional cut lumber

FEATURES AND BENEFITS

Low VOC, easy application and clean-up, low odor, greater worker safety to traditional solvent based systems.

PACKAGING

18.9 L Pail, 205 L Drums, 1000 L Totes

TINT AND BASE INFORMATION

Clear and custom colors

PRODUCT DATA

Gloss: Flat – Low Gloss VOC: 370 g/l Coverage: Approx. 320 sqft / gal at 1mil DFT DFT: 2 mil or greater recommended Weight-Volume: Approximately 1.1 kg/ litre Volume-Solids: Approximately 22% solids by volume Weight-Solids: Approximately 33% solids by weight Drying Time: (@ 25°C) To Touch: 30 min., Recoat: 1 hour Clean up: Clean with soap and water

DISCLAIMER

The technical data furnished above by the Consolidated Coatings Company is provided for information purposes only and is, to the best of our knowledge. Since application methods and conditions are beyond our control, we cannot offer a guarantee or warranty, representation, or condition, express or implied, whether arising by statute, by operation of law, or otherwise, (including merchantability or fitness for a particular purpose) with respect to this product and we assume no responsibility or liability of any kind for coverage, performance or damage (whether arising from negligence of the vendor or otherwise) resulting from the installation, operation, use or performance of this product.

MIXING & APPLICATION INFORMATION

Mix thoroughly, component A with component B on a 1:1 ratio, let stand Mix thoroughly before and during use. Air or airless spray application is recommended. (Airless: 2100 psi with 0.015"- 0.017" tip) (Brush: Natural Bristle Brush) (Roller: Limited use, 9-10mm nap, solvent resistant core) Thinning is not required for

most applications.

SAFETY

Proper safety procedures should be followed at all times while handling this product. In confined areas, personal protection equipment should be used.

GENERAL SURFACE PREPARATION

The surface to be coated must be dry, clean and free of oil, grease, release agents and foreign material.

LIMITATIONS OF USE

Apply only when ambient and surface temperatures are above 10 degrees Celsius.

DISPOSAL

Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.



7651 Vantage Way, Delta, BC, Canada, V4G 1A6 T: 604-946-7626 | F: 604-946-9609 | TF: 1-800-663-5690