

date of prep : 26/10/16

SECTION I

manufacturer : Consolidated Coatings Corporation

address : #310 7651 Vantage Way  
Delta, British Columbia  
V4G 1A6

telephone# : 604-946-7626

emergency# :

- H M I S -

HEALTH	: 2
FLAMMABILITY	: 3
REACTIVITY	: 0
PERSONAL PROTECT.:	G

whmis class : B,D2B

(HAZARD RATING : 0=least, 1=slight, 2=moderate, 3=high, 4=extreme, \*=chronic)

mfg. code id : 1-60-1206 MSDS revision# : 200027

(G = safety glasses, gloves, & vapor respirator)

trade name : COAL TAR EPOXY PT.A [1:1]

SECTION II-A

HAZARDOUS COMPONENTS

no.	component	CAS#	% by wt.	SARA	vapor pressure (mm Hg @ 20 C)	LEL (@ 25 C)
1	METHYL ETHYL KETONE	78-93-3	1 - 5	YES	70.20	1.80
2	TOLUENE	108-88-3	5 - 10	YES	47.00	1.40
3	XYLENE	1330-20-7	5 - 10	YES	6.60	1.10
4	REFINED COAL TAR	65996-93-2	35 - 40	NO	N/A	1.00
5	TALC	14807-96-6	20 - 25	NO	N/A	N/A
6	SILICEOUS MUSCOVITE MICA	12001-26-2	1 - 5	NO	N/A	N/A
7	AMORPHOUS SILICA GEL	7631-86-9	1 - 5	NO	N/A	N/A
8	TETRAETHYLENEPENTAMINE	112-57-2	5 - 10	NO	N/A	N/A

>> Component number 4 is listed by NTP, OSHA and IARC as a carcinogen or a possible carcinogen.

Please refer to appropriate reference sources for carcinogenicity information.

>> Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372, chemicals listed on the Section 313 List (40 CFR Part 373.65) are identified under the heading 'SARA 313'.

(N/A = not applicable)

SECTION II-B

OCCUPATIONAL EXPOSURE LIMITS

no.	(OSHA) PEL/TWA	PEL/CEILING	PEL/STEL	skin
1	200 ppm	300 ppm	N/E	N/E
2	200 ppm	300ppm,500ppm 10m/8hr	N/E	N/E
3	100 ppm / 434 mg/m3	N/E	N/E	N/E
4	N/E	N/E	N/E	N/E
5	20 mppcf	N/E	N/E	N/E
6	20 mppcf	N/E	N/E	N/E
7	20 mppcf	N/E	N/E	N/E
8	N/E	N/E	N/E	N/E

no.	(ACGIH) TLV/TWA	TLV/CEILING	TLV/STEL	skin
1	590 ppm	885 ppM	N/E	N/E
2	100 ppm	N/E	150 ppm	N/E
3	100 ppm / 434 mg/m3	N/E	N/E	N/E
4	N/E	N/E	N/E	N/E
5	2 mg/m3 Resp. Dust	N/E	N/E	N/E
6	3 mg/m3 Respirable Dus	N/E	t	N/E
7	10 mg/m3 Total Dust	N/E	N/E	N/E
8	N/E	N/E	N/E	N/E

>> The dried film of this product may become a dust nuisance when removed by sanding or grinding. OSHA recommends a PEL/TWA of 15 mg/m3 for total dust and 5 mg/m3 for the respirable fraction. ACGIH recommends a TLV/TWA of 10 mg/m3 for total dust.

>> (SKIN) absorpition may contribute to the overall exposure to this material. Take appropriate measures to prevent skin contact.  
(N/E = not established)

SECTION III

PHYSICAL DATA

boiling point	: not established	% volatile by volume	: 34.74 (Theoretical)
evaporation rate	: < 1 (ether = 1)	% volatile by weight	: 22.19 (Theoretical)
vapor density	: > 1 (air = 1)	kilograms per liter	: 1.275 (Theoretical)

SECTION IV

HEALTH INFORMATION

EYE CONTACT

BASED ON THE PRESENCE OF COMPONENT 8 PRODUCT IS PRESUMED TO BE CORROSIVE TO THE EYES. EXPOSURE MAY CAUSE CHEMICAL BURNS AND EXTENSIVE CORNEAL INJURY. BASED ON THE PRESENCE OF COMPONENTS 1, 2 AND 3 PRODUCT VAPORS AND/OR MISTS MAY ALSO BE IRRITATING TO THE EYES.

SKIN CONTACT

BASED ON THE PRESENCE OF COMPONENT 8 PRODUCT IS PRESUMED TO BE CORROSIVE TO THE SKIN AND EXPOSURE MAY CAUSE CHEMICAL BURNS. BASED ON THE PRESENCE OF COMPONENTS 1, 2 AND 3 PROLONGED OR REPEATED CONTACT MAY RESULT IN DEFATTING AND DRYING OF THE SKIN WHICH MAY RESULT IN DERMATITIS. BASED ON THE PRESENCE OF COMPONENT 8 CONTACT WITH THE SKIN MAY RESULT IN SKIN SENSITIZATION TO AMINES, POLYAMINES, POLYAMIDES AND RELATED COMPOUNDS. INDIVIDUALS WHO HAVE DEVELOPED A SKIN SENSITIZATION CAN DEVELOP THESE SYMPTOMS AS A RESULT OF CONTACT WITH VERY SMALL AMOUNTS OF LIQUID MATERIAL OR AS A RESULT OF EXPOSURE TO VAPOR. THIS SKIN SENSITIZATION MAY BE TEMPORARY OR PERMANENT. ONCE AN INDIVIDUAL IS DIAGNOSED AS BEING SENSITIZED, NO FURTHER EXPOSURE CAN BE PERMITTED. BASED ON THE PRESENCE OF COMPONENT 4 PRODUCT CAN CAUSE SKIN IRRITATION AND DERMATITIS, INCLUDING ACNE. COAL TAR IS A PHOTOTOXIC SUBSTANCE WHICH, IN THE PRESENCE OF ULTRAVIOLET LIGHT (SUNLIGHT) CAN CAUSE A SKIN REACTION SIMILAR TO AN EXAGGERATED SUNBURN, FREQUENTLY CAUSING BLISTERS.

INHALATION

EXPOSURE MAY PRODUCE IRRITATION TO THE NOSE, THROAT, RESPIRATORY TRACT, AND OTHER MUCOUS MEMBRANES. BASED ON THE PRESENCE OF COMPONENTS 1, 2 AND 3 EXPOSURE TO HIGH CONCENTRATIONS OF VAPOR MAY PRODUCE CENTRAL NERVOUS SYSTEM DEPRESSION. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

INGESTION

BASED ON THE PRESENCE OF COMPONENT 1 PRODUCT IS PRESUMED TO BE MODERATELY TOXIC. BASED ON THE PRESENCE OF COMPONENT 2 INGESTION MAY CAUSE KIDNEY DAMAGE. BASED ON THE PRESENCE OF COMPONENT 2 INGESTION MAY CAUSE LIVER DAMAGE. BASED ON THE PRESENCE OF COMPONENTS 2 AND 3 SMALL AMOUNTS OF THE LIQUID ASPIRATED INTO THE LUNGS DURING INGESTION OR FROM VOMITING MAY RESULT IN SEVERE LUNG DAMAGE. BASED ON THE PRESENCE OF COMPONENTS 1, 2 AND 3 INGESTION MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION.

SIGNS AND SYMPTOMS

SYMPTOMS OF EYE IRRITATION INCLUDE PAIN, TEARING, REDDENING AND SWELLING. SYMPTOMS OF SKIN IRRITATION INCLUDE REDDENING, SWELLING, RASH AND REDNESS. SYMPTOMS OF RESPIRATORY IRRITATION INCLUDE RUNNY NOSE, SORE THROAT, COUGHING, CHEST DISCOMFORT, SHORTNESS OF BREATH AND REDUCED LUNG FUNCTION. SYMPTOMS OF GASTROINTESTINAL IRRITATION INCLUDE SORE THROAT, ABDOMINAL PAIN, NAUSEA, VOMITING AND DIARRHEA. BASED ON THE PRESENCE OF COMPONENTS 1, 2 AND 3 CENTRAL NERVOUS SYSTEM DEPRESSION MAY BE EVIDENCED BY HEADACHE, DIZZINESS, NAUSEA AND SYMPTOMS OF INTOXICATION; IN EXTREME CASES, UNCONSCIOUSNESS AND DEATH MAY OCCUR. SYMPTOMS OF CHRONIC OVEREXPOSURE INCLUDE LOSS OF MEMORY, LOSS OF INTELLECTUAL ABILITY AND LOSS OF COORDINATION.

AGGRAVATED MEDICAL CONDITIONS

PREEXISTING SKIN, EYE AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. IMPAIRED CENTRAL NERVOUS SYSTEM FUNCTIONS FROM PREEXISTING DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

OTHER HEALTH EFFECTS

BASED ON THE PRESENCE OF COMPONENT 1 PRODUCT IS PRESUMED TO BE FETOTOXIC. BASED ON THE PRESENCE OF COMPONENT 2 CHRONIC OVEREXPOSURE MAY CAUSE INJURY TO THE BONE MARROW AND BLOOD CELLS. BASED ON THE PRESENCE OF COMPONENT 2 CHRONIC OVEREXPOSURE MAY CAUSE INJURY TO THE KIDNEYS AND LIVER. BASED ON THE PRESENCE OF COMPONENT 2 CHRONIC OVEREXPOSURE MAY CAUSE DAMAGE TO THE RED BLOOD CELLS. BASED ON THE PRESENCE OF COMPONENT 2 CHRONIC OVEREXPOSURE MAY CAUSE DAMAGE TO THE KIDNEYS. BASED ON THE PRESENCE OF COMPONENT 7 CHRONIC OVEREXPOSURE TO AMORPHOUS SILICA DUST MAY CAUSE A TISSUE RESPONSE (PNEUMOCONIOSIS). BASED ON THE PRESENCE OF COMPONENT 5 CHRONIC OVEREXPOSURE TO TALC DUST MAY CAUSE SCARRING OF THE LUNGS.

SECTION V

EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT

IMMEDIATELY FLUSH EYES WITH COPIOUS AMOUNTS OF WATER FOR AT LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. SEEK PROMPT MEDICAL ATTENTION.

SKIN CONTACT

IMMEDIATELY REMOVE CONTAMINATED CLOTHING AND SHOES. WIPE EXCESS FROM SKIN AND FLUSH WITH WATER FOR AT LEAST 15 MINUTES USING SOAP IF AVAILABLE. SEEK PROMPT MEDICAL ATTENTION. DO NOT REUSE CLOTHING UNTIL THOROUGHLY DECONTAMINATED.

INHALATION

REMOVE VICTIM TO FRESH AIR AND TREAT SYMPTOMATICALLY. PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GIVE ARTIFICIAL RESPIRATION IF THE VICTIM IS NOT BREATHING. SEEK PROMPT MEDICAL ATTENTION.

INGESTION

DO NOT INDUCE VOMITING. IF VOMITING SPONTANEOUSLY OCCURS, KEEP THE VICTIM'S HEAD BELOW THE HIPS TO PREVENT ASPIRATION INTO THE LUNGS. SINCE ASPIRATION INTO THE LUNGS CAN CAUSE VERY SERIOUS, PERMANENT DAMAGE, THE DECISION OF WHETHER TO INDUCE VOMITING OR NOT SHOULD BE MADE BY A PHYSICIAN. DANGER FROM LUNG ASPIRATION MUST BE WEIGHED AGAINST TOXICITY WHEN CONSIDERING EMPTYING THE STOMACH. CONSULT A PHYSICIAN, HOSPITAL OR POISON CONTROL CENTER AND/OR TRANSPORT TO AN EMERGENCY FACILITY IMMEDIATELY.

>> COMPONENTS 2 AND 3 DO NOT INDUCE VOMITING.

