

date of prep : 01/11/16

1-6T-0898 (page 1)

SECTION I

manufacturer : Consolidated Coatings Corporation
 address : #310 7651 Vantage Way
 Delta, British Columbia
 V4G 1A6
 telephone# : 604-946-7626
 emergency# :

- H M I S -

HEALTH	: 1
FLAMMABILITY	: 0
REACTIVITY	: 0
PERSONAL PROTECT.:	C

whmis class : D2B (HAZARD RATING : 0=least, 1=slight, 2=moderate, 3=high, 4=extreme, *=chronic)
 mfg. code id : 1-6T-0898 MSDS revision# : 26003 (C = safety glasses, gloves, & synthetic apron)
 trade name : HOUDINI INK, RED

SECTION II-A

HAZARDOUS COMPONENTS

no.	component	CAS#	% by wt.	SARA	vapor pressure (mm Hg @ 20 C)	LEL (@ 25 C)
1	2-AMINO-2-METHYL-1-PROPANOL	124-68-5	1 - 5	NO	<1.00 @ 25 C	N/A

>> None of the components of this product are recognized as carcinogenic.

(N/A = not applicable)

SECTION II-B

OCCUPATIONAL EXPOSURE LIMITS

no.	(OSHA) PEL/TWA	PEL/CEILING	PEL/STEL	skin
1	N/E	N/E	N/E	N/E

no.	(ACGIH) TLV/TWA	TLV/CEILING	TLV/STEL	skin
1	N/E	N/E	N/E	N/E

>> The dried film of this product may become a dust nuisance when removed by sanding or grinding. OSHA recommends a PEL/TWA of 15 mg/m3 for total dust and 5 mg/m3 for the respirable fraction. ACGIH recommends a TLV/TWA of 10 mg/m3 for total dust.

>> (SKIN) absorption may contribute to the overall exposure to this material. Take appropriate measures to prevent skin contact.
 (N/E = not established)

SECTION III

PHYSICAL DATA

boiling point	: not established	% volatile by volume	: 97.01 (Theoretical)
evaporation rate	: < 1 (ether = 1)	% volatile by weight	: 96.88 (Theoretical)
vapor density	: > 1 (air = 1)	kilograms per liter	: 1.001 (Theoretical)

SECTION IV

HEALTH INFORMATION

EYE CONTACT

BASED ON THE PRESENCE OF COMPONENT 1 PRODUCT IS PRESUMED TO BE SEVERELY IRRITATING TO THE EYES. EXPOSURE MAY CAUSE EXTENSIVE CORNEAL INJURY.

SKIN CONTACT

BASED ON THE PRESENCE OF COMPONENT 1 PRODUCT IS PRESUMED TO BE CORROSIVE TO THE SKIN AND EXPOSURE MAY CAUSE CHEMICAL BURNS.

INHALATION

EXPOSURE MAY PRODUCE IRRITATION TO THE NOSE, THROAT, RESPIRATORY TRACT, AND OTHER MUCOUS MEMBRANES.

INGESTION

BASED ON THE PRESENCE OF COMPONENT 1 PRODUCT IS PRESUMED TO BE MODERATELY TOXIC.

SIGNS AND SYMPTOMS

SYMPTOMS OF EYE IRRITATION INCLUDE PAIN, TEARING, REDDENING AND SWELLING. SYMPTOMS OF SKIN IRRITATION INCLUDE REDDENING, SWELLING, RASH AND REDNESS. SYMPTOMS OF RESPIRATORY IRRITATION INCLUDE RUNNY NOSE, SORE THROAT, COUGHING, CHEST DISCOMFORT, SHORTNESS OF BREATH AND REDUCED LUNG FUNCTION. SYMPTOMS OR GASTROINTESTINAL IRRITATION INCLUDE SORE THROAT, ABDOMINAL PAIN, NAUSEA, VOMITING AND DIARRHEA.

AGGRAVATED MEDICAL CONDITIONS

PREEXISTING SKIN, EYE AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

OTHER HEALTH EFFECTS

NONE RECOGNIZED.

=====

SECTION V EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT

IMMEDIATELY FLUSH EYES WITH COPIOUS AMOUNTS OF WATER FOR AT LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. SEEK PROMPT MEDICAL ATTENTION.

SKIN CONTACT

REMOVE CONTAMINATED CLOTHING AND SHOES. WIPE EXCESS FROM SKIN AND FLUSH WITH WATER USING SOAP IF AVAILABLE. SEEK MEDICAL ATTENTION IF IRRITATION OCCURS. DO NOT REUSE CLOTHING UNTIL THOROUGHLY DECONTAMINATED. CONTAMINATED LEATHER ARTICLES CANNOT BE DECONTAMINATED AND SHOULD BE DISPOSED.

INHALATION

REMOVE VICTIM TO FRESH AIR AND TREAT SYMPTOMATICALLY. PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GIVE ARTIFICIAL RESPIRATION IF THE VICTIM IS NOT BREATHING. SEEK PROMPT MEDICAL ATTENTION.

INGESTION

DO NOT INDUCE VOMITING. VOMITING WILL CAUSE FURTHER DAMAGE TO THE THROAT. DILUTE BY GIVING WATER OR MILK TO DRINK IF THE VICTIM IS CONSCIOUS. CONSULT A PHYSICIAN, HOSPITAL OR POISON CONTROL CENTER AND/OR TRANSPORT TO AN EMERGENCY FACILITY IMMEDIATELY.

=====

SECTION VI FIRE AND EXPLOSION HAZARDS

flammability classification - OSHA : COMBUSTIBLE LIQUID - CLASS IIIB

- DOT : NOT REGULATED

flash point : 200 DEGREES C

EXTINGUISHING MEDIA

USE WATER FOG, FOAM, DRY CHEMICAL OR CARBON DIOXIDE.

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS

CLEAR FIRE AREA OF UNPROTECTED PERSONNEL. DO NOT ENTER CONFINED FIRE SPACE WITHOUT HELMET, FACE SHIELD, BUNKER COAT, GLOVES, RUBBER BOOTS, AND A POSITIVE PRESSURE NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE AND EXPLOSION HAZARDS

CONTAINERS EXPOSED TO INTENSE HEAT FROM FIRES SHOULD BE COOLED WITH WATER TO PREVENT VAPOR PRESSURE BUILDUP WHICH COULD RESULT IN CONTAINER RUPTURE. CONTAINER AREAS EXPOSED TO DIRECT FLAME CONTACT SHOULD BE COOLED WITH LARGE QUANTITIES OF WATER AS NEEDED TO PREVENT WEAKENING OF CONTAINER STRUCTURE.

=====
SECTION VII

REACTIVITY

STABILITY : STABLE

HAZARDOUS POLYMERIZATION : WILL NOT OCCUR

CONDITIONS AND MATERIALS TO AVOID
NONE RECOGNIZED.

HAZARDOUS DECOMPOSITION PRODUCTS
OXIDES AND COMPOUNDS OF NITROGEN, CARBON DIOXIDE, CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

=====
SECTION VIII

EMPLOYEE PROTECTION

RESPIRATORY PROTECTION
USE VENTILATION AS REQUIRED TO CONTROL VAPOR CONCENTRATIONS - AT LEAST 10 AIR CHANGES PER HOUR ARE RECOMMENDED FOR GOOD GENERAL ROOM VENTILATION. IF EXPOSURE EXCEEDS THE PEL/TLV, USE THE APPROPRIATE NIOSH-APPROVED RESPIRATOR.

PROTECTIVE CLOTHING
WEAR SAFETY GLASSES, GOGGLES, OR A SPLASH SHIELD TO PREVENT EYE CONTACT. CONTACT LENSES SHOULD NOT BE WORN. WEAR NEOPRENE OR OTHER CHEMICAL RESISTANT GLOVES TO PREVENT SKIN CONTACT.

ADDITIONAL PROTECTIVE MEASURES
EYE WASH FOUNTAINS AND SAFETY SHOWERS SHOULD BE AVAILABLE FOR USE IN AN EMERGENCY.

=====
SECTION IX

ENVIRONMENTAL PROTECTION

SPILL OR LEAK PROCEDURES
LARGE SPILLS >> EVACUATE THE HAZARD AREA OF UNPROTECTED PERSONNEL. WEAR APPROPRIATE RESPIRATOR AND PROTECTIVE CLOTHING. SHUT OFF SOURCE OF LEAK ONLY IF SAFE TO DO SO. DIKE AND CONTAIN. IF VAPOR CLOUD FORMS, WATER FOG MAY BE USED TO SUPPRESS; CONTAIN RUN-OFF. REMOVE WITH VACUUM TRUCKS OR PUMP TO STORAGE/SALVAGE VESSELS. SOAK UP RESIDUE WITH AN ABSORBENT SUCH AS CLAY, SAND OR OTHER SUITABLE MATERIAL; PLACE IN NON-LEAKING CONTAINERS FOR PROPER DISPOSAL. FLUSH AREA WITH WATER TO REMOVE TRACE RESIDUE; DISPOSE OF FLUSH SOLUTIONS AS ABOVE. SMALL SPILLS >> TAKE UP WITH AN ABSORBENT MATERIAL AND PLACE IN NON-LEAKING CONTAINERS; SEAL TIGHTLY FOR PROPER DISPOSAL.

WASTE DISPOSAL
OBSERVE ALL FEDERAL, PROVINCIAL, AND LOCAL REGULATIONS REGARDING PROPER DISPOSAL OF WASTE MATERIAL.

=====
SECTION X

ADDITIONAL PRECAUTIONS

CONTAINERS CAN CONTAIN HAZARDOUS PRODUCT RESIDUES EVEN WHEN EMPTY. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, OR USING TOILET FACILITIES.

=====
THE INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVILABLE TO US AND IS BELIEVED TO BE CORRECT. HOWEVER, WE MAKE NO WARRANTY, EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. WE ASSUME NO RESPONSIBILITY FOR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.
=====