

# **MAGI-MARK STAMPING INK**

Product Data Sheet (Revised 24/11/21)

## **PRODUCT CATEGORY**

Industrial - Wood

## **PRODUCT CODE**

6T-0782 – Magi-Mark Ink | RED 6T-2190 – Magi-Mark Ink | BLUE 6T-0781 – Magi-Mark Ink | GREEN 6T-0779 – Magi-Mark Ink | BLACK

# **DESCRIPTION**

Magi-Mark Stamp Ink is a ready to use stamping ink used to mark and indicate grade on dimensional lumber and engineered lumber and board. This ink is used in roller stamp systems as an identification for lumber.

# **RECOMMENDED USE**

Used as a part of a roller stamp system to mark lumber for identification purposes. Can be used as an ink for hand stamping lumber.

# **FEATURES AND BENEFITS**

Ready to use formulation and stand out colors for easy visibility.

# **PACKAGING**

3.7 L Bottle, 18.9 L Pail

## **PRODUCT DATA**

**Color:** Red, Blue, Green, Black **Viscosity:** Greater than water

Weight-Volume: Approximately 1.0 kg/litre

Storage: Keep from freezing, keep out of direct sunlight

#### DISCLAIMER

The technical data furnished above by the Consolidated Coatings Company is provided for information purposes only and is, to the best of our knowledge. Since application methods and conditions are beyond our control, we cannot offer a guarantee or warranty, representation, or condition, express or implied, whether arising by statute, by operation of law, or otherwise, (including merchantability or fitness for a particular purpose) with respect to this product and we assume no responsibility or liability of any kind for coverage, performance or damage (whether arising from negligence of the vendor or otherwise) resulting from the installation, operation, use or performance of this product.

## **MIXING & APPLICATION INFORMATION**

Mix thoroughly before and during use.

## **SAFETY**

Proper safety procedures should always be followed while handling this product. In confined areas, personal protection equipment should be used.

## **GENERAL SURFACE PREPARATION**

The surface to be coated must be dry, clean and free of oil, grease, release agents and foreign material.

## **CLEAN-UP**

Clean with soap and water

#### **SHELF LIFE**

2 years maximum-unopened

#### DISPOSAL

Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

