

ACRYLIC URETHANE REACTOR (Part B)

Product Data Sheet (Revised 0/03/22)

PRODUCT CATEGORY

High Performance Coatings - Industrial

PRODUCT CODE

52-2000 Part A White, 52-2010 Part B Urethane Reactor.

DESCRIPTION

A top quality HDI Trimer. Designed for use with 52-2000, 52-2005, 52-2015 and 52-2020. Easy 4:1 by volume mix ratio.

RECOMMENDED USE

This acrylic urethane may be used for exterior or interior industrial maintenance, transportation, marine and product finishing applications where corrosion resistance and long-term protection are important. May be used on various metal substrates, wood, plastics and concrete.

May be blended with Industrial Enamel: 74-0800 series at ½ pint per gallon to increase surface hardness and mar resistance.

PACKAGING

18.9 L Pail

COLOUR

Clear

PRODUCT DATA

Gloss: Not applicable

VO: 850 g/l

Coverage: Not applicable

Solids: 79.1% by weight, 74.2% by volume.

Weight: 1.088 Kg/L.

Flash Point: 27.2° (81°F)

Drying Time: Not applicable

Clean Up: 85-0337 Reducer

GENERAL SURFACE PREPARATION

Surface to be painted must be clean, dry and free of oil, grease and other contamination.

MIXING: Mix 4 volumes of Part A with one volume of Part B. Pot life about 4 hours.

APPLICATION: Spray apply with conventional or airless equipment.

THINNING: Thin with 85-0337 reducer as required.

RECOMMENDED FILM THICKNESS: Not Applicable

NUMBER OF COATS: Not Applicable.

LIMITATIONS OF USE

Apply only when ambient and surface temperatures are above 10 degrees Celsius. For professional use only. Immediately after use place rags, steel wool and waste soaked with the product in a water filled metal container.

MIXING AND APPLICATION INFORMATION

Mix 4 volumes of Part A with one volume of Part B. Pot life about 4 hours.

SAFETY

Please refer to the Material Safety Data Sheet for information on the safe handling of this product.

DISCLAIMER

The technical data furnished above by the Consolidated Coatings Company is provided for information purposes only and is, to the best of our knowledge. Since application methods and conditions are beyond our control, we cannot offer a guarantee or warranty, representation, or condition, express or implied, whether arising by statute, by operation of law, or otherwise, (including merchantability or fitness for a particular purpose) with respect to this product and we assume no responsibility or liability of any kind for coverage, performance or damage (whether arising from negligence of the