

TRIPLE A ANTIFOULING

Technical Data Sheet

Date of issue: 01/10/2023

Product Category

Anti-fouling Paint

Product Code

64-0862

Description

A high quality copper based antifouling paint, registration number 21985 under the Pest Control Products Act.

Recommended Use

Triple A antifouling paint may be used directly on metal steel hulls, wood or fiberglass hulls to reduce marine fouling.

Packaging

3.78 can and 18.9 L Pail

Product Data

Color: Red

Gloss: flat

Volume Solid: 50% \pm 2%

Weight solid: 75% \pm 2%

Recommended Film Thickness

1 mil DFT per coat. 2 coats recommended.

Practical Coverage

17 m² /liter/coat for DFT at 1 mil, based on the loss factor of 15%. Actual coverage may vary depending on the type, age and texture of the substrate and application method.

Dry time at 20 °C

4 hours between coats, minimum 2 hours before launching following application of final coat.

Surface Preparation

Surface to be painted must be clean, dry, and free of oil, grease, and other contamination.

For previously painted surfaces, remove loose paint by 80 grade (grit) paper or sandblasting, wipe with 85-0311 reducer.

Application Conditions

Apply when temperature is above 10 °C.

Launching

Prolonged exposure to air affects the performance of antifouling paints. Launch within 24 hours of application of last coat. For earlier launching, allow 2 hours for last coat to dry.

Clean-up Solvent

85-0311 Reducer

Disposal

Contact your local environmental regulatory agency for guidance on disposal of unused product.

Disclaimer

The technical data furnished above by the Consolidated Coatings Company is provided for information purposes only and is, to the best of our knowledge. Since application methods and conditions are beyond our control, we cannot offer a guarantee or warranty, representation, or condition, express or implied, whether arising by statute, by operation of law, or otherwise, (including merchantability or fitness for a particular purpose) with respect to this product and we assume no responsibility or liability of any kind for coverage, performance or damage (whether arising from negligence of the vendor or otherwise) resulting from the installation, operation, use or performance of this product.